

J1PS-DA

10.4" Touch Screen LCD Monitor

Product Specifications

SPECIFICATIONS		J1PS-DA
LCD Display Area		10.4" TFT active matrix panel
Display Size (HxV)		8.3"x6.2" (210.4x157.8mm)
Pixel Pitch (HxV)		0.2055x0.2055mm
Max. Resolution		SVGA 800 X 600
Contrast Ratio		300:1 (typical)
Brightness		230 cd/m ² (typical)
Response Time		25 ms
Display Color		262K
Viewing Angle	L/R	110°
	U/D	+35°~-15° (typical)
Input Signal	Video	RGB Analog 0.7Vp-p
	Sync	TTL Positive or Negative
Display Mode		VGA 720x400 (70 Hz) VGA 640x480 (60/66/70/72/75/85 Hz) SVGA 800x600 (60/70/72/75/85 Hz)
Signal Connector	Analog	15 pin D-sub
Front Control		Power on/off with LED, Menu/Select, Adjustment (+,-)
Plug & Play		DDC1/2B compatible
Power Adapter		Input AC 90~264V, 50~60Hz; Output DC 12V / 3.5A
Operating Conditions	Temperature	41°F ~ 95°F (5°C ~ 35°C)
	Humidity	20% ~ 80% (no condensation)
	Altitude	To 10,000 Feet
Storage Conditions	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
	Humidity	10% ~ 90% (no condensation)
Audio System	Speakers	1W/per channel driver
Dimensions (HxWxD)		9.25"x10.8"x1.75" (235x274x44.5mm)
Weight (Net)		6.6lb (3kg)
Touch Option		Resistive or Capacitive
Optional Module		Wall mount, robotic arm, pole mount kit, black bezel
Certification		CE, FCC, UL

Specifications are subject to change without notice.



Catch the wave of the future!

20532 Crescent Bay Dr. Suite 104
 Lake Forest, CA 92630
 Ph: 949-586-3338 Fax: 949-586-3398
 www.gvision-usa.com

