

# L5EX 15" LCD Monitor

## Product Specifications

### SPECIFICATIONS

### L5EX

LCD Display Area		15.0" TFT Active Matrix Panel
Display Size (HxV)		12"x9" (304x228mm)
Pixel Pitch (HxV)		0.297x0.297mm
Max. Resolution		XGA 1024x768
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m <sup>2</sup> (typical)
Response Time		30 ms
Display Color		16M
Viewing Angle	L/R	140°
	U/D	140°
Input Signal	Video	RGB analog 0.7V peak to peak
	Sync	TTL Positive or Negative
Display Mode		VGA 720x400 (70 Hz) VGA 640x480 (60/66/70/72/75 Hz) SVGA 800x600 (60/70/72/75 Hz) XGA 1024x768 (60/70/75 Hz)
Signal Connector	Analog	D-sub 15 pin
Front Control	Power on/off with LED, Menu, Select, Adjustment (+,-)	
OSD	Brightness, Contrast, Clock, Phase, Auto-tune, H-position, V-position, RGB color drive, OSD format, Volume	
Plug and Play	DDC1/2B compatible	
Power	Embedded AC input power system, universal 90-264 Volts	
Operating Conditions	Temperature	32°F~104°F ( 0°C~40°C)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
	Humidity	10%-80% (no condensation)
Audio System	Speakers	1W/per channel driver
Dimensions (HxWxD)	15.3"x14.9"x3.0" (388.3x378.2x76.2mm)	
Weight (Net)	12.1lb (5.5kg)	
Optional Module	Touch panel, adjustable arm	
Certifications	C-UL, FCC, TUV/GS, CE, MPR II, EPA, NUTEK, D, N, S, F, TCO (optional)	

Specifications are subject to change without notice.



**Catch the wave of the future!**

20532 Crescent Bay Dr. Suite 104  
Lake Forest, CA 92630  
Ph: 949-586-3338 Fax: 949-586-3398  
www.gvision-usa.com

