

L2ES-DA

12.1" LCD Monitor

Product Specifications

SPECIFICATIONS

L2ES-DA

LCD Display Area		12.1" TFT Active Matrix Panel
Display Size (HxV)		9.7"x7.3" (246 x 184.5mm)
Pixel Pitch (HxV)		0.3075 x 0.3075mm
Max. Resolution		SVGA 800x600
Contrast Ratio		250:1 (typical)
Brightness		200 cd/m ² (typical)
Response Time		30 ms (typical)
Display Color		262K
Viewing Angle	L/R	80° (typical)
	U/D	+20°~-10° (typical)
Input Signal	Video	RGB Analog 0.7Vp-p
	Sync	TTL Positive or Negative
Display Mode		VGA 640X350 (70/85 Hz)
		VGA 720X400 (70/85Hz)
		VGA 640X480 (60/72/75/85 Hz)
		SVGA 800x600 (56/60/72/75/85 Hz)
		Mac. 832 x 624 (75Hz)
Signal Connector	Analog	D-sub 15 pin
Front Control	Power on/off with LED, Menu, Select, Adjustment (Up, Down)	
OSD	Brightness, Contrast, RGB Contrast, Auto Setup, Frequency, Phase H-/V-position, Track, Expansion, Display Mode, Recall, Text/Graphics	
Plug & Play	DDC1/2B compatible	
Power Adapter	Input AC 90-264V, 50-60Hz; Output DC 12V/3.5A	
Operating Conditions	Temperature	41°F ~ 104°F (5°C ~ 40°C)
	Humidity	20% ~ 80% (no condensation)
	Altitude	To 10,000 Feet
Storage Conditions	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
	Humidity	10% ~ 90% (no condensation)
Video-In	Optional Video-In (Model # L2ES-DW)	
Dimensions (HxWxD)	9.3"x12.3"x2.9" (236x312x73.7mm)	
Weight (Net)	6.6lb (3.0kg)	
Optional Module	Black bezel	
Certifications	C-UL, FCC, CE	

Specifications are subject to change without notice.



Catch the wave of the future!

20532 Crescent Bay Dr. Suite 104

Lake Forest, CA 92630

Ph: 949-586-3338 Fax: 949-586-3398

www.gvision-usa.com



Revised 10/03