



MicroTouch™ M170 LCD Touch Monitor

TOUCH MONITORS



Product Highlights

- 400 cd/m², 450:1 contrast ratio TFT LCD panel
- Peripheral Attachment System
- Maximum touch stability
- DVI-I digital and 15 pin D-sub analog video support
- User-lockable on screen display controls
- Locking display adjustment
- Warranty: 3-year FPD, 5-year touch sensor and components
- Proven 3M touch technology

Designed to be Different

The MicroTouch™ M170 Touch Monitor from 3M was designed to be different. The result of extensive customer research, innovative industrial design, and years of touch technology expertise, the M170 monitor's unique mechanical and technology features offer premium performance for a wide-range of implementations.

- Remarkable touch stability provided by multiple, wide attachment points between the base and display, a unique unified strut support system, and a positive locking mechanism on the display angle adjustment.
- Display angle adjustable within a 95° range.
- Out-of-the-box wall mountable
- Easily secured to wall or countertop by keyhole slots in the sturdy steel baseplate.
- Peripheral Attachment System – Mount your preferred peripheral device or simultaneously mount multiple peripheral devices.
- Accepts both analog and DVI input.
- High quality TFT LCD panel delivers crisp, bright viewing from almost any angle.
 - 400 cd/m² brightness
 - 450:1 contrast ratio
 - 160° x 160° viewing cone
- Cables, connections and power supply are all concealed, and peripheral cables can be concealed as well.
- Complete multimedia package, lockable on-screen display controls, and full VESA-mounting compliance.

The Right Touch

The MicroTouch M170 touch monitor is offered with a choice of MicroTouch 5-wire resistive technology or MicroTouch ClearTek™ capacitive touch technology to meet the unique demands of your application.

Specifications

MicroTouch™ M170 LCD Touch Monitor

17" LCD

FUNCTIONAL FEATURES

LCD Technology	TFT, Active Matrix
Display Colors	16M
Pixel Pitch	.264 mm
Brightness without touch screen	400 cd/m ² typical
Brightness with touch screen (max.)¹	344 cd/m ² typical
Contrast Ratio	450:1 typical
Response Time	16 ms typical
Viewing Angle (from center)	Horizontal: 160 degrees total typical Vertical: 160 degrees total typical
Front Panel Buttons	Menu, Select, Adjust, Power
On Screen Display Controls	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Auto Config., Color, Recall
Maximum Resolution	1280 x 1024
Number of Allowable Unlit Pixels	10
Operating Environment	Operating Temperature: 0 to 50 degrees C Relative Humidity, Non-condensing 95%
Storage Environment	-20 to +60 degrees C

PHYSICAL FEATURES

Physical Dimensions (WxHxD)	405 x 413.3 x 247 mm 15.9 x 16.3 x 9.7 inches
Display Area (WxH)	338.5 x 270.5 mm 13.3 x 10.6 inches
Video Cable Connector	15-pin D-sub, and DVI
Power Supply	12V DC Power Supply
Power Savings²	DPMS, VESA Compliant
Power Consumption	25W, Normal Operation
Backlight Life	40,000 hrs. typical
Weight (Net)	8.6 kg/18.9 lbs.
Agency Approvals	FCC B, CE, UL/cUL, C-Tick, VCCI, CCC
Mounting Options	VESA mounting compatible, 100mm
Multimedia	Full multimedia capability
Color Option	Beige, Black
Controller Option³	Serial, USB
Warranty	3 Years FPD 5 Years Touch Sensor and Components

(1) Brightness measured using MicroTouch capacitive C-etch sensor.

(2) DPMS: Display power management signaling for reduced power consumption during non-use.

(3) USB Option, call for availability.

NOTICE: Given the variety of factors that can affect the use and performance of a 3M Touch Systems Product (the "Product"), including that solid state equipment has operation characteristics different from electromechanical equipment, some of which factors are uniquely within User's knowledge and control, it is essential that User evaluate the 3M Touch Systems Product and software to determine whether it is suitable for User's particular purpose and suitable for User's method of application. 3M Touch Systems' statements, engineering/technical information, and recommendations are provided for User's convenience, but their accuracy or completeness is not warranted. 3M Touch Systems products and software are not specifically designed for use in medical devices as defined by United States federal law. 3M Touch Systems products and software should not be used in such applications without 3M Touch Systems' express written consent. User should contact its sales representative if User's opportunity involves a medical device application.

IMPORTANT NOTICE TO PURCHASER: Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. **3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose.** User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software media or to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. **3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)**



3M Touch Systems
3M Optical Systems Division
 300 Griffin Brook Park Drive
 Methuen, MA 01844
 U.S.A.

Worldwide Manufacturing Plants:
 Methuen, Massachusetts
 Milwaukee, Wisconsin
 Vancouver, BC Canada

**For more information on 3M touch products,
 visit 3Mtouch.com or call toll-free 1-866-407-6666**

www.3Mtouch.com

MicroTouch and ClearTek are registered trademarks
 of 3M Company.

Printed in USA
 © 3M 2004
 M170FPD-2-04



Peripheral attachment system



"Cable-Through-Bottom" routing option for
 seamless counter or wall installation



Wall-mounted
 configuration