

POS X

POINT OF SALE
PERFECTED

Xr510 SERIES

HI-SPEED THERMAL RECEIPT PRINTER

The Xr510 next generation Hi-Speed Thermal Receipt Printer sets the bar in performance and price. The Xr510 has been redesigned from the inside to operate day-in and day-out in the harshest of environments that require steadfast performance. Perfect for high-volume retail and hospitality operations, the Xr510 features 33% faster printing, JamFree Autocutter Technology, and now includes the interface cable standard with all models.




KEY FEATURES

- Multiple Interfaces: USB, PAR, RS232, Ethernet
- 7.9" (200mm) per Second Print Speed
- ESC/POS and OPOS compatible
- Drop-in thermal paper loading
- JamFree Autocutter Technology
- Swappable interface cards
- Interface cable included
- Wall mountable
- 3-Year warranty

receipt printer

Xr510 Series Specifications

PART NUMBER	XR510U	XR510P	XR510S	XR510E
SPECIFICATIONS				
Interfaces	USB	Parallel	Serial	Ethernet
Interface Details	USB 2.0	IEEE-1.284	RS-232C	10/100
Emulation	ESC/POS Command Compatible			
Print Method	Direct Thermal			
Printing Speed	7.9"/sec 200mm/sec			
Dot Density	180 DPI x 180 DPI			
Dot Pitch	0.005551" x 0.005551"			
Printing Direction	Unidirectional with Friction Feed			
Sensors	Paper End, Cover Open, Paper Low, Black Mark			
CASH DRAWER PORTS	2 Circuits (24V, 1A max)			
RELIABILITY	TPH Life 62.14 miles MCBF 60,000,000 Lines			
PAPER				
Type	Thermal Paper			
Width	1.9" (50mm) - 3.125" (82.5mm)			
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)			
Roll Diameter	Max 3.27" (83mm)			
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019 "(0.5mm)			
CHARACTER SET	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14			
CHARACTER/LINE	Font A (12 x24) 42 columns		Font B (9 x17) 56 columns	
BARCODES SUPPORTED	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128,PDF 417(2D)			
AUTO CUTTER				
Type	JamFree auto-retracting Guillotine			
Life	1,000,000 Cuts			
Cutting Method	Full/Partial Cut			
PHYSICAL				
Dimension	6.1"(W) x 7.60"(D) x 5.80"(H)			
Weight	3.53 lbs			
Color	Black			
ELECTRICAL	(input)100 - 240 Vac 50/50 Hz		(output) 24Vdc/2.5A	
ENVIROMENTAL				
Temperature	41° F to 104° F operating -4° F to 140° F storage			
Humidity	35%-80% non condensing (operation)		10%-90% non condensing (storage)	
WARRANTY	3 Year		1 year on autocutter assembly and print head	
CERTIFICATIONS	FCC, MIC, UL, CE, CCC, RoHs			
OPERATING SYSTEM	WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/OPOS driver available			



ACCESSORIES

XR-PCARD	Parallel Interface Card for XR210, XR510, and XR500
XR-SCARD	Serial Interface Card for XR210, XR510, and XR500
XR-UCARD	USB Interface Card for XR210, XR510, and XR500
XR-ECARD	Ethernet Interface Card for XR210, XR510, and XR500
XR-510-RR	3 Year Rapid Replacement Warranty